# PROJOINT ELIMINATOR

ELIMINATE CROVI PAZE,
CEMENTIFOR RESPONSE

SUBJECT OF THE SECOT

SLOW STATE OF THE SECON

SLOW S

PROCLEAN TECHNOLOGY

# **PREPARATION:**

PAVING SHOULD BE SOUND AND FREE FROM LOOSE DEBRIS. SURFACES CAN BE DAMP PRIOR TO APPLICATION, BUT THIS MAY AFFECT THE PERFORMANCE ON THE SOLUTION AS IT WILL DILUTE FURTHER FROM THE EXTRA WATER.
RATIOS:

LIGHT DEPOSITS ON NON-ABSORBENT SURFACES - 1 PART ELIMINATOR TO 4 PARTS COLD, CLEAN WATER.

HEAVY DEPOSITS - 1 PART ELIMINATOR TO 1 PART WATER.

EXTREME CASES - PRE-WET AFFECTED AREA WITH WATER AND APPLY ELIMINATOR NEAT.

### **APPLICATION INSTRUCTIONS:**

1: WEARING APPROPRIATE PPE, ADD PROJOINT ELMINATOR TO APPROPRIATE RATIO OF WATER AS REQUIRED (SEE DILUTION RATIOS ABOVE) AND MIX GENTLY. 2A: LIGHT DEPOSITS - APPLY SOLUTION WITH CLOTH OR SPONGE, LEAVE FOR A MAXIMUM 30 MINUTES AND EXTRACT RESIDUES WITH SPONGE AND WATER. 2B: HEAVY DEPOSITS - LIBERALLY APPLY SOLUTION AND AGITATE WITH SCRUBBING BRUSH OR ROTARY SCRUBBING MACHINE, LEAVE FOR 5-10 MINUTES KEEPING SURFACE WETTED WITH SOLUTION IF NEEDED. EXTRACT AND RINSE WITH CLEAN WATER. 2C: EXTREME CASES - PRE-WET AREA WITH WATER AND APPLY ELIMINATOR NEAT, AGITATE AREA AND IMMEDIATLEY EXTRACT AND RINSE WITH WATER

IMPORTANT: ALWAYS TEST IN A HIDDEN AREA PRIOR TO USE AND ONLY PROCEED WHEN SATISFIED WITH THE RESULTS. THE TECHNICAL INFORMATION SUPPLIED IS BASED ON DATA OBTAINED BY OUR OWN RESEARCH AND IS CONSIDERED ACCURATE. HOWEVER, NO LIABILITY IS ACCEPTED FOR ANY LOSS OR DAMAGE ARISING DIRECTLY OR INDIRECTLY FROM THE USE OF OUR PRODUCTS, OR FROM THE INFORMATION GIVEN IN PUBLICATIONS. PROSPECTIVE USERS SHOULD THEREFORE SATISFY THEMSELVES BY APPROPRIATE TRIALS THAT THE PRODUCT IS SUITABLE FOR THE

INTENDED USE. DO NOT DISCHARGE WASTE INTO DRAINS OR RIVERS.







DANGER

# **KEY FACTS:**



FOR ALL UNPOLISHED NATURAL STONE AND PORCELAIN SURFACES (INCLUDING SENSITIVE STONES LIKE BLACK LIMESTONE)

WATER-BASED - CAN BE USED ALL YEAR ROUND

ACID REPLACEMENT TECHNOLOGY (CONTAINS NO BRICK ACID)

PERFECT FOR ALL INTERIOR AND EXTERIOR WALLS/FLOORS

OIY FRIENDLY, DOESN'T DAMAGE SURROUNDING MATERIALS

REMOVES CEMENT DEPOSITS IN MINUTES

SYSTEM	WATER BASED GROUT HAZE, CEMENTITOUS RESIDUE, EFFLORESENCE AND SALTS ELIMINATOR
STORAGE	STORE IN A COOL, DRY, AND FROST FREE ENVIRONMENT AT TEMPERATURES BETWEEN 5°C AND 30°C
SHELF LIFE	12 MONTH FROM DATE OF MANUFACTURE
PACKAGING	1LTR AND 5LTR CONTAINERS
DILUTION	LIGHT - 1:4 HEAVY - 1:1 EXTREME - UNDILUTED
WORKING TIME	0-30 MINUTES DEPENDENT ON DILUTION AND AMBIENT TEMPRATURES

## KEEP OUT OF THE REACH OF CHILDREN

**HAZARD STATEMENTS:** Causes skin irritation. Causes serious eye damage.

PRECAUTIONARY STATEMENTS: Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection. IF ON SKIN: Wash with plenty of water/soap. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE/doctor If skin irritation occurs: Get medical advice/attention. Dispose of contents/container to a licensed waste centre in accordance with local/regional/national/international regulations.

STORAGE: Store in closed, labelled containers.

**COVERAGE:** This product covers approximately

\*per litre depending on substrate porosity.

\*Light deposits: 25m<sup>2</sup>

\*Heavy deposits: 15m2

\*Undiluted: 5m<sup>2</sup>



**BRUTE STRENGTH PAVING PRODUCTS**