

TECH DATA SHEET

PROJOINTTM PRE-GROUT PROFESSIONAL PAVING SEALER



PRODUCT INFORMATION

PROJOINT PRE-GROUT PAVING SEALER is a water based pre-grout treatment for all types of porcelain, natural stone or concrete paving whether it is inside or out.

Designed to help with grout or jointing compound release, the PRE-GROUT PAVING SEALER should be used once the paving has been firmly laid in position upon a suitable bedding area.

The PRE-GROUT PAVING SEALER can also be used once any grouting has been completed, and is fully cured, to protect the paving and aid with the removal of stains and dirt from organic matter.

DIRECTIONS FOR USE

Paving should be sound, clean and free from dirt, dust, oil, etc. Surfaces can be damp prior to application, but a better seal would be achieved if the paving is dry. We recommend cleaning with Nexus Paving & Driveway Cleaner prior to application and leave to dry for at least two days. It is very important that the paving is left to allow all moisture within the paving to disappear.

The PRE-GROUT SEALER is designed as an invisible coating but may darken very light surfaces slightly. As with all sealants, test on a small inconspicuous area before full application. The sealer is supplied ready for use and should be applied when the surface temperature of the paving is between 5°C and 25°C. As a guide, the stone should be cool to the touch.

Shake the container well prior to use. Application may be made by brush, roller or spray (ensuring appropriate PPE is worn). Apply a complete, even coat over the whole surface ensuring any excess is removed – allow to dry for 30 minutes. Apply a second even coat and leave to cure. Dependent on temperature, this second coat should be fully cured in around 1 hour (an extra coat may be required on porous paving).

Once the sealer has fully cured, the paving can be grouted/pointed. For additional temporary grout protection a final coat can be applied. For a longer lasting seal we recommend using the PRO-820 ECO INVISIBLE WATER-BASED SEALER once the PRE-GROUT SEALER

has faded. All tools/equipment should be thoroughly cleaned with water after use.


HEALTH AND SAFETY ADVISORY

CONTAINS: 2-METHYLISOTHIAZOL-3(2H)-ONE
May cause an allergic skin reaction. Keep out of reach of children and animals.

Wear protective gloves/protective clothing/ eye protection/face protection.

IF ON SKIN: Wash with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention.

STORAGE: The PROJOINT PRE-GROUT PAVING SEALER should be stored in sealed containers in a cool, dry and frost-free environment, protected from extremes of temperature.



SYSTEM	WATER BASED INVISIBLE PAVING SEALER FOR NATURAL STONE, CONCRETE AND PORCELAIN PAVERS
STORAGE	STORE IN A COOL, DRY, AND FROST FREE ENVIRONMENT AT TEMPERATURES BETWEEN 5°C AND 30°C
SHELF LIFE	12 MONTH FROM DATE OF MANUFACTURE
PACKAGING	1 LITRE & 5 LITRE TUBS DELIVERED ON SHRINK-WRAPPED PACKAGING
PALLET QUANTITY	N/A
COVERAGE	UP TO 15M ² PER LITRE ON NATURAL STONE, 30M ² PER LITRE ON PORCELAIN
COLOURS	N/A
WALK ON CURING TIME	IMMEDIATELY AFTER SURFACE DRY
FULL STRENGTH	N/A
SUB BASE REQUIREMENT	N/A

KEY FACTS:

- ✓ EASY AND FAST APPLICATION
- ✓ WATER BASED FORMULA FOR ALL YEAR ROUND APPLICATION
- ✓ HIGH COVERAGE RATE FOR STONE AND PORCELAIN PAVING
- ✓ IDEAL FOR ALL TYPES OF TEXTURED PORCELAIN TILES
- ✓ PERFECT FOR USE WITH ALL PROJOINT GROUTING PRODUCTS
- ✓ ASSISTS IN REDUCING RESIN SHEEN AND GROUT HAZE

APPROXIMATE COVERAGE PER LITRE

Depending on substrate porosity, this product covers up to:

15m² per litre when applied to natural stone or concrete
30m² per litre on porcelain.

'formulated for
natural stone,
porcelain & concrete
paving...'



BRUTE STRENGTH PAVING PRODUCTS