

TECH DATA SHEET

PROJOINT PRO410

COLOUR ENHANCING PAVING SEALER
PROFESSIONAL SOLVENT BASED

PROSEAL TECHNOLOGY



PREPARATION:

SUBSTRATES SHOULD BE SOUND, CLEAN AND FREE FROM DIRT, DUST, OIL, ETC AND MUST BE TOTALLY DRY. WE RECOMMEND CLEANING WITH PROJOINT PAVING & DRIVEWAY CLEANER PRIOR TO APPLICATION AND LEAVE TO DRY FOR AT LEAST TWO DAYS. **IT IS VERY IMPORTANT** THAT FRESHLY LAID PAVING IS LEFT A MINIMUM OF 8 WEEKS TO ALLOW ALL MOISTURE WITHIN THE PAVING TO DISAPPEAR. AS WITH ALL SEALANTS, TEST ON A SMALL INCONSPICUOUS AREA BEFORE FULL APPLICATION. THE SEALER IS SUPPLIED READY FOR USE AND SHOULD BE APPLIED WHEN THE SURFACE TEMPERATURE OF THE PAVING IS BETWEEN 5°C AND 25°C. AS A GUIDE, THE STONE SHOULD BE COOL TO THE TOUCH.

APPLICATION INSTRUCTIONS:

1: WEARING APPROPRIATE PPE, APPLY PROJOINT PRO-410 EVENLY USING A FOAM ROLLER, PAINT BRUSH, OR A LOW-PRESSURE SPRAYER, ENSURING EXCESS IS REMOVED. **2:** ALLOW TO DRY (UP TO 2 HOURS DRYING TIME) **2A:** IF REPEAT APPLICATION IS REQUIRED FOR FURTHER ENHANCED COLOUR & PROTECTION, PLEASE ALLOW 6-8 HOURS UNTIL APPLYING A SECOND COAT. **3:** ALL TOOLS/EQUIPMENT SHOULD BE THOROUGHLY CLEANED WITH A SUITABLE SOLVENT SUCH AS WHITE SPIRIT AFTER USE.

IMPORTANT: ALWAYS TEST IN A HIDDEN AREA PRIOR TO USE AND ONLY PROCEED WHEN SATISFIED WITH THE RESULTS. THE TECHNICAL INFORMATION SUPPLIED IS BASED ON DATA OBTAINED BY OUR OWN RESEARCH AND IS CONSIDERED ACCURATE. HOWEVER, NO LIABILITY IS ACCEPTED FOR ANY LOSS OR DAMAGE ARISING DIRECTLY OR INDIRECTLY FROM THE USE OF OUR PRODUCTS, OR FROM THE INFORMATION GIVEN IN PUBLICATIONS. PROSPECTIVE USERS SHOULD THEREFORE SATISFY THEMSELVES BY APPROPRIATE TRIALS THAT THE PRODUCT IS SUITABLE FOR THE INTENDED USE. DO NOT DISCHARGE WASTE INTO DRAINS OR RIVERS.

SYSTEM	SOLVENT BASED MATT FINISH SEALER
STORAGE	STORE COOL, AND DRY AT TEMPERATURES BETWEEN 5°C AND 25°C
SHELF LIFE	12 MONTH FROM DATE OF MANUFACTURE
PACKAGING	1LTR, 5LTR AND 25LTR CONTAINERS
DRYING TIME	UP TO 2 HOURS IN DRY AMBIENT CONDITIONS
CURING TIME	UP TO 24 HOURS IN DRY AMBIENT CONDITIONS
COVERAGE	APPROXIMATELY 4.5-7SQM PER LTR



KEY FACTS:

- ✓ PROFESSIONAL GRADE WATER REPELLENT FOR POROUS NATURAL STONE AND CONCRETE
- ✓ BREATHABLE, ENHANCES, SEALS AND PROTECTS
- ✓ RESISTS DIRT, GRIME AND ALGAE
- ✓ LONG LASTING PROTECTION AND UV STABLE MATT FINISH
- ✓ HIGH SURFACE PENETRATION
- ✓ SINGLE COAT WITH HIGH COVERAGE RATE

KEEP OUT OF THE REACH OF CHILDREN AND ANIMALS

MAY PRODUCE AN ALLERGIC REACTION

HAZARD STATEMENTS: H226: FLAMMABLE LIQUID AND VAPOUR.

H304: MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

H315: CAUSES SKIN IRRITATION.

H335: MAY CAUSE RESPIRATORY IRRITATION.

H336: MAY CAUSE DROWSINESS OR DIZZINESS.

H411: TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

EUH066: REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.

PRECAUTIONARY STATEMENTS:

P210: KEEP AWAY FROM HEAT, HOT SURFACES, SPARKS, OPEN FLAMES AND OTHER IGNITION SOURCES. NO SMOKING.

P233: KEEP CONTAINER TIGHTLY CLOSED.

P243: TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGE.

P301+310:

IF SWALLOWED:

IMMEDIATELY CALL A POISON CENTER/DOCTOR OR MEDICAL PRACTITIONER.

P304+ 340: IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING.

P241: USE EXPLOSION PROOF ELECTRICAL/VENTILATING/ LIGHTING EQUIPMENT.

P280: WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION/FACE PROTECTION.

P303+361+353:

IF ON SKIN (OR HAIR): TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/ SHOWER.

P403+233: STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED.

P235: KEEP COOL.

UN NUMBER: 1993 TRANSPORT CLASS: 3 PACKING GROUP: III

STORAGE: STORE IN SEALED CONTAINERS PROTECTED

FROM FROST AND EXTREMES OF TEMPERATURE.

COVERAGE: THIS PRODUCT COVERS APPROXIMATELY 4.5 TO 7M2 PER LITRE DEPENDING ON SUBSTRATE POROSITY.

BRUTE STRENGTH PAVING PRODUCTS

